

# MACHINE SPECIFICATIONS



© Woodstock International, Inc. • Phone: (800) 840-8420 • Web: www.shopfox.biz

## MODEL W1729 2 HP 19" BANDSAW

### Product Dimensions

Weight..... 367 lbs.  
Width (side-to-side) x Depth (front-to-back) x Height..... 36 x 32 x 76 in.  
Footprint (Length x Width)..... 29-1/2 x 17-3/4 in.

### Shipping Dimensions

Type..... Wood Slat Crate  
Content..... Machine  
Weight..... 435 lbs.  
Length x Width x Height..... 21 x 33 x 84 in.  
Must Ship Upright..... Yes

### Electrical

Power Requirement..... 115V or 230V, Single-Phase, 60 Hz  
Prewired Voltage..... 230V  
Full-Load Current Rating..... 20A at 115V, 10A at 230V  
Minimum Circuit Size..... 30A at 115V, 15A at 230V  
Connection Type..... Cord & Plug  
Power Cord Included..... Yes  
Power Cord Length..... 72 in.  
Plug Included..... Yes  
Included Plug Type..... 6-15 for 230V  
Recommended Plug Type..... L5-30 for 115V  
Switch Type..... Push Button ON/OFF Switch

### Motors

#### Main

Horsepower..... 2 HP  
Phase..... Single-Phase  
Amps..... 20A/10A  
Speed..... 1725 RPM  
Type..... TEFC Capacitor-Start Induction  
Power Transfer ..... V-Belt Drive  
Bearings..... Shielded & Permanently Lubricated  
Centrifugal Switch/Contacts Type..... External

### Main Specifications

#### Main Specifications

Bandsaw Size..... 19 in.  
Max Cutting Width (Left of Blade)..... 18-1/4 in.  
Max Cutting Width (Left of Blade) w/Fence..... 16-5/8 in.  
Max Cutting Height (Resaw Height)..... 12 in.  
Blade Speeds..... 1700, 3500 FPM

**Blade Information**

Standard Blade Length..... 143 in.  
Blade Length Range..... 141-1/2 - 143 in.  
Blade Width Range..... 1/8 - 1 in.  
Type of Blade Guides..... Roller Disc  
Guide Post Adjustment Type..... Rack & Pinion  
Has Quick-Release..... Yes

**Table Information**

Table Length..... 26-3/4 in.  
Table Width..... 19 in.  
Table Thickness..... 1-1/2 in.  
Table Tilt..... Left 5, Right 45 deg.  
Table Tilt Adjustment Type..... Manual  
Floor-to-Table Height..... 37-1/2 in.  
Fence Locking Position..... Front  
Fence is Adjustable for Blade Lead..... Yes  
Resaw Fence Attachment Included..... No  
Miter Gauge Included..... Yes

**Construction Materials**

Table..... Precision Ground Cast Iron  
Trunnion..... Steel  
Fence..... Deluxe Extruded Aluminum  
Base/Stand..... Pre-Formed Steel  
Frame/Body..... Pre-Formed Steel  
Wheels..... Computer-Balanced Cast Iron  
Tire..... Polyurethane  
Wheel Cover ..... Pre-Formed Steel  
Paint Type/Finish..... Powder Coated

**Other Related Information**

Wheel Diameter..... 18-7/8 in.  
Wheel Width..... 1-1/4 in.  
Number of Dust Ports..... 2  
Dust Port Size..... 4 in.  
Compatible Mobile Base..... D2058A

**Other**

Country of Origin ..... Taiwan  
Warranty ..... 2 Years  
Approximate Assembly & Setup Time ..... 1 Hour  
Serial Number Location ..... Label on Top Cover  
ISO 9001 Factory ..... Yes  
Certified by a Nationally Recognized Testing Laboratory (NRTL) ..... Yes

**Features**

Hinged Wheel Covers with Safety Lock  
Quick Change Blade Release/Tensioner  
Magnifying Window on Fence Scale  
Height Scale Measurement  
Miter Gauge  
Blade Tension Indicator  
Rack and Pinion Upper Guide Adjustment