

MACHINE SPECIFICATIONS



Phone #: (360) 734-3482 • Online Tech Support: tech-support@shopfox.biz • Web: www.shopfox.biz

MODEL W1755 6" PARALLELOGRAM JOINTER

Motor

Type TEFC Capacitor Start Induction
Horsepower 1 1/2 HP
Phase / Voltage Single-Phase / 110V/220V
Amps 15A/7.5A
Cycle / RPM..... 60 Hertz / 3450 RPM
Switch Push Button w/Oversized OFF Button
Power Transfer.....Belt Drive
Bearings Sealed and Lubricated for Life

Capacity

Maximum Depth of Cut (per pass) 1/8"
Maximum Width of Cut 6"
Cutterhead Speed 4850 RPM
Cuts Per Minute 19,400

Overall Dimensions

Table Size 6" W X 55 1/2" L
Height (from floor to table) 32 1/2"
Overall Length 55 1/2"
Overall Width..... 24 1/2"
Shipping Weight..... 347 lbs.
Net Weight..... 320 lbs.
Box #1 Size..... 63" x 22" x 14"
Box #2 Size..... 29" x 20" x 28"
Stand Footprint 27" x 20 1/2"
Cutterhead..... 4-Knife
Cutterhead Diameter..... 3"
Cutterhead Knife Size..... 6" x 3/4" x 1/8"

Construction

Tables Precision Ground Cast Iron
Fence Assembly Cast Iron
Body Assembly Cast Iron
Stand..... Steel
Guard Aluminum
Bearings Sealed and Lubricated for Life

Features

Parallelogram-Style Tables
Top Mount Switch Controls
Built-In Mobile Base
5" Tall Fence
Included Push Blocks
Included Knife Setting Jig