

MACHINE SPECIFICATIONS



© Woodstock International, Inc. • Phone: (800) 840-8420 • Web: www.shopfox.biz

MODEL W1865 20" PLANER WITH HELICAL CUTTERHEAD, 5HP

Product Dimensions

Weight..... 772 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 44 x 56 x 45 in.
Footprint (Length x Width)..... 27-1/2 x 23 in.

Shipping Dimensions

Type..... Wood Crate
Content..... Machine
Weight..... 882 lbs.
Length x Width x Height..... 45 x 30 x 46 in.
Must Ship Upright..... Yes

Electrical

Power Requirement..... 220V, Single-Phase, 60 Hz
Prewired Voltage..... 220V
Full-Load Current Rating..... 23A
Minimum Circuit Size..... 30A
Connection Type..... Cord & Plug
Power Cord Included..... Yes
Power Cord Length..... 10 ft.
Power Cord Gauge..... 12 AWG
Plug Included..... Yes
Included Plug Type..... L6-30
Switch Type..... Button Controls w/Magnetic Switch Protection

Motors

Main

Horsepower..... 5 HP
Phase..... Single-Phase
Amps..... 23A
Speed..... 3450 RPM
Type..... TEFC Capacitor-Start Induction
Power Transfer Triple V-Belt Drive
Bearings..... Shielded & Permanently Lubricated
Centrifugal Switch/Contacts Type..... External

Main Specifications

Main Specifications

Planer Size.....	20 in.
Max. Cut Width.....	20 in.
Min. Stock Length.....	7 in.
Min. Stock Thickness.....	1/4 in.
Max. Stock Thickness.....	8 in.
Number of Cuts Per Inch.....	83, 104
Number of Cuts Per Minute.....	20,000
Cutterhead Speed.....	5000 RPM
Planing Feed Rate.....	16, 28 FPM
Max. Cut Depth Planing Full Width.....	5/64 in.
Max. Cut Depth Planing 6-Inch Wide Board.....	1/8 in.

Cutterhead Info

Cutterhead Type.....	Helical
Cutterhead Diameter	3-1/4 in.
Number of Cutter Rows.....	4
Number of Indexable Cutters.....	92
Cutter Insert Size Length.....	15 mm
Cutter Insert Size Width.....	15 mm
Cutter Insert Size Thickness.....	2.5 mm

Table Info

Table/Headstock Movement.....	8 in.
Table Bed Size Length.....	56 in.
Table Bed Size Width.....	20 in.
Table Bed Size Thickness.....	2-1/4 in.
Number of Bed Rollers.....	2
Floor-to-Table Height.....	28 - 36 in.

Construction

Table.....	Precision-Ground Cast Iron
Body.....	Cast Iron
Stand.....	Steel
Cutterhead Assembly.....	Steel
Infeed Roller.....	Serrated Steel
Outfeed Roller.....	Smooth Steel
Paint Type/Finish.....	Powder Coated

Other

Table/Headstock Locks.....	Yes
Measurement Scale.....	Inch & Metric
Number of Dust Ports.....	1
Dust Port Size.....	5 in.
Mobile Base.....	D2058A

Other

Country of Origin	Taiwan
Warranty	2 Years
Approximate Assembly & Setup Time	2 Hours
Serial Number Location	ID Label on Upper Cover
ISO 9001 Factory	Yes
Certified by a Nationally Recognized Testing Laboratory (NRTL)	Yes

Features

- Extra-Large Ball-Bearing Return Rollers
- Large Side-Mounted Handwheel
- Cabinet Style Stand
- Internally Mounted 5HP Motor
- Triple V-Belt Drive
- Pedestal-Mounted Control Panel with E-Stop & Magnetic Switch Protection
- 4 Heavy-Duty Headstock Support Columns
- Anti-Kickback Fingers
- Oil-Bath Style Gearbox for Drive System
- Triple Belt Drive Inside Housing
- Heavy-Duty Cast-Iron Extension Wings
- Helical Cutterhead with Indexable Carbide Inserts
- Powder-Coated Finish